



EVC10 Mode 3 ISO/IEC 15118



UV Pure PC material, Anti-UV treatment, and over 3 years' yellow resistance

AI ISO/IEC 15118 plug & charge

IK08 & IP54 enclosure for indoor & outdoor use

LAN LAN standard, 4G or Wi-Fi optional

32A to 16A by switch, 32A to 6A by TCP server

OCPP 1.6J, Successfully connected with 30+ global EVC platforms

OPEN solution for UK, Integrated MID for 1 phase, 3-ph & 1-ph compatible

4.3" LCD screen for better user experience (QR code available)

Model No.	JNT-EVC10/AC07	JNT-EVC10/AC11	JNT-EVC10/AC22
Input Voltage	230Vac±10%	400Vac±10%	
Frequency	50-60Hz		
Amperage	32A	16A	32A
Max. Power Output	7kW	11kW	22kW
Net Weight (Cable/Socket)	5.2kg / 3.7kg	4.9kg / 3.9kg	6.5kg / 3.9kg
Gross Weight (Cable/Socket)	6.3kg / 4.7kg	6.0kg / 4.9kg	7.6kg / 4.9kg
Product Dimensions	351 x 250 x 130mm (Cable) / 351 x 250 x 155mm (Socket)		
Package Dimensions	497 x 348 x 272mm (Cable) / 444 x 324 x 215mm (Socket)		
Protection & Standard			
Charging Interface	IEC 62196-2 Compliant, Type 2 Socket or Plug		
Safety Compliance	IEC 61851-1, IEC 61851-21-2		
Multiple Protection	UVP, OVP, RCD (DC 6mA), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection		
Environmental			
Operating Temperature	-30°C ~ 50°C		
Relative Humidity	Up to 95% non-condensing		
Cable Length	5m Standard Cable (7m Optional with Surcharge)		