



**EVC12 Mode 3 7KW~22KW**



Pure PC material, Anti-UV treatment, and over 3 years' yellow resistance

OPEN solution available for UK

IK08 & IP54 enclosure for indoor & outdoor use

Wi-Fi & Bluetooth + APP control

32A to 16A by switch, 32A to 6A by TCP server

OCPP 1.6J optional

Integrated MID for 1 phase 3 phase & 1 phase compatible

ISO/IEC 15118 available in Q2, 2022

Model No.	JNT-EVC12/AC07	JNT-EVC12/AC11	JNT-EVC12/AC22
Input Voltage	230Vac±10%	400Vac±10%	
Frequency	50-60Hz		
Amperage	32A	16A	32A
Max. Power Output	7kW	11kW	22kW
Net Weight	4.8kg	4.5kg	5.8kg
Gross Weight	5.8kg	5.5kg	6.8kg
Product Dimensions	351 x 250 x 111.5mm		
Package Dimensions	497 x 348 x 252mm		
Protection & Standard			
Charging Interface	IEC 62196-2 Compliant, Type 2 Plug		
Safety Compliance	IEC 61851-1, IEC 61851-21-2		
Multiple Protection	UVP, OVP, RCD (DC 6mA), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection		
Environmental			
Operating Temperature	-30°C ~ 50°C		
Relative Humidity	Up to 95% non-condensing		
Cable Length	5m Standard Cable (7m Optional with Surcharge)		